


Reelcraft 9000

Veergewonden, zeer stabiele, hoog volume haspel, geschikt voor slang van 1/2" tot en met 1 1/2"
Zeer goede corrosiebestendigheid doordat alle delen zijn gepoedercoat. **Exclusief slang.**



Model	9305	9200	9300	9400
	mm.	mm.	mm.	mm.
A	667	667	667	667
B	613	613	613	613
C	114	121	121	121
D	340	305	305	305
E	195	195	195	195
F	556	556	556	556
G	311	311	311	311
H	352	352	352	352
J	670	670	670	670



Veergewonden, zonder slang.
Maximum temperatuur +99 °C.

artikelnr.	model	inlaat bi.dr."	uitgang bi.dr. "	Ø slang mm.	lengte mtr.	werkdruk bar	gewicht kg.
9D9200OLP	D9200 OLPBW	1/2	1/2	13	30	35	53
9D9300OLP	D9300 OLPBW	3/4	3/4	19	23	35	53
9D9305OLP	D9305 OLPBW	3/4	3/4	19	30	35	53
9D9400OLP	D9400 OLPBW	1	1	25	15	35	53
9D9200OMP	D9200 OMPBW	1/2	1/2	13	23	207	54
9D9300OMP	D9300 OMPBW	3/4	3/4	19	15	207	54